GS72M-540-560

Half Cell Monocrystalline 144 Cells 540W-560W

FEATURES

INCREASE POWER OUTPUT
0~+5W power guarantee

ENHANCED POWER OUTPUT
Temperature coefficient of maximum power: -0.35%/℃

REDUCE OCCLUSION LOSS
Very little chance of hot spots, ensuring safe power generation of modules

STRONGER MECHANICAL LOAD
2400pa reverse load, 5400pa front mechanical load

LINEAR PERFORMANCE WARRANTY



15 Years Product Warranty

25 Years Power Warranty

The first year≤3%, 2-25 years≤0.55%/year

info@giftsunsolar.com
+86 185 5588 6666

ENGINEERING DRAWINGS



MECHANICAL CHARACTERISTICS

Cell Type	Mono 182x91mm
Weight(kg)	27kg
Glass Thickness	3.2mm
Dimensions (L*W*H)(mm)	2279x1134x35mm
Cable Cross Section Size (mm²)	4mm²
No.of Cells and Connections	144(6x24)
Junction Box	IP68
Connector	MC4 Compatiple

WORKING CONDITION

Maximum System Voltage	DC 1000V/1500V
Operating Temperature	-40℃~ +85℃
Maximum Series Fuse	25A
Maximum Static Load,Front (e.g.,snow and wind)	5400Pa
Maximum Static Load,Back (e.g.,wind)	2400Pa
NOCT	45±2℃
Application Class	Class A

PACKAGING CONFIGURATION

Moduels Per Pallet	31Pcs
Moduels Per 40HQ	620Pcs

SPECIFICATIONS

Module	GS72M-540-560				
	STC	STC	STC	STC	STC
Maximum Power Pmax (W)	540	545	550	555	560
Maximum Power Voltage (Vmp/V)	41.64	41.80	41.96	42.11	42.27
Maximum Power Current (Imp/A)	12.97	13.04	13.11	13.18	13.25
Open Circuit Voltage (Voc/V)	49.60	49.75	49.90	50.02	50.15
Short Circuit Current (Isc/A)	13.86	13.93	14.00	14.07	14.14
Module Efficiency (%)	20.90	21.10	21.30	21.50	21.70
Temperature Coefficient of Isc (αIsc)	+0.043%/℃				
Temperature Coefficient of Voc (βVoc)	-0.26%/℃				
Temperature Coefficient of Pmax (γPmp)	-0.36%/℃				
STC	Irradiance 800W/㎡, Cell Temperature 20℃, Air Mass 1.5				

CHARACTERISTIC CURVE





info@giftsunsolar.com
+86 185 5588 6666